

## TW30W-PRB

### 30" Oscillating OSHA Pedestal Fan



Air Velocity (@ 10') :	1100	Guard Color :	White
Blade Color :	Metallic	Guard Material & Coating :	Powder Coated Steel
Blade Material :	Aluminum	Guard Spacing (inches) :	1/2 OSHA
Brand :	Schaefer	Max RPM :	1075
CFM (free air) :	9600	Mount Type Included :	Pedestal
CFM (high) :	9600	Mount Type Recommended :	NA
CFM (low) :	8500	Nameplate Amps :	5.9
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Number of Wings :	3
CFM Range (Free Air) :	5001 - 10000	Opening Area (sq. ft.) :	NA
CFM/Watt (free Air) :	19.7	Oscillating :	Yes
CFM/Watt Range (free air) :	15.1 - 20	Phase :	1
Component Certifications :	Motor - UL/CSA/CE	Power (hp) :	1/2
Cord :	Included - Wired	Rough-in Dimensions :	NA
Cord Length (feet) :	10	Schaefer Performance Test No. :	701
Country of Origin :	US	Sound Level (dBA @ 10') :	71
Description :	30" Oscillating Circulation Fan, White OSHA Guards, Black Round Pedestal	Speed Control Compatible :	No
Diameter (inches) :	30	Speeds :	2
Drive Type :	Direct	Switch :	On product
Fixed or Portable :	Portable	VFD Compatible :	No
Frequency (Hz) :	60	Voltage :	115