

20CFO-B

20" Circulation Fan



| | | | |
|-----------------------------|---------------------------|---|--------------------|
| Able to Ship Small Parcel : | Yes | Guard Spacing (inches) : | 1/2 OSHA |
| Blade Color : | Metallic | Max RPM : | 1100 |
| Blade Material : | Aluminum | Mount Type Recommended : | WMTA24-B, VS24FMT |
| CFM (high) : | 4050 | Nameplate Amps : | 2.9/1.6 |
| CFM (low) : | 3000 | Number of Wings : | 3 |
| CFM Calculation Standard : | ANSI/AMCA Standard 230-99 | Oscillating : | No |
| CFM Range (Free Air) : | 2501 - 5000 | Phase : | 1 |
| CFM/Watt (free Air) : | 17.7 | Power (hp) : | 1/4 |
| Component Certifications : | Motor - CSA | Product Color : | Black |
| Cord : | Included - Wired | Product Dimensions (L x W x H inches) : | 22.5 x 6.25 x 12in |
| Cord Length (feet) : | 10 | Product Shipping Dimensions : | 24 X 24 X 13 |
| Country of Origin : | US | Product Weight (pounds) : | 30 |
| Diameter (inches) : | 20 | Schaefer Performance Test No. : | 101 |
| Display Name : | 20CFO-B | Speed Control Compatible : | No |
| Drive Type : | Direct | Speeds : | 2 |
| Fixed or Portable : | Fixed | Switch : | On product |
| Frequency (Hz) : | 60 | VFD Compatible : | No |
| Guard Color : | Black | Voltage : | 115 |
| Guard Material & Coating : | Powder Coated Steel | | |