


## 543SMCB112G-HV

54" Exhaust Fan Surface Mount with Cone and Butterfly Shutter - High Volume



Able to Ship Small Parcel :	No	Fixed or Portable :	Fixed
BESS Lab Performance Test No. :	13281	Frequency (Hz) :	60
Blade Color :	Metallic	Guard Color :	Metallic
Blade Material :	Galvanized Steel	Guard Material & Coating :	Galvanized Steel
Blade Pitch (degrees) :	32	Hardware Included :	Yes
Bore Size (inches) :	1	Housing Color :	Metallic
CFM (@0.05") :	30800	Housing Material :	Galvanized Steel
CFM (@ 0.10") :	29200	Material :	Galvanized Steel
CFM (free air) :	32600	Motor Mounting :	Base
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Nameplate Amps :	6.8-6.4
CFM Range (Free Air) :	>30000	Number of Wings :	3
CFM/Watt (@0.05") :	21.1	Phase :	1
CFM/Watt (@0.10") :	18.9	Power (hp) :	1 1/2
CFM/Watt (free Air) :	23.3	Product Color :	Metallic
Component Certifications :	Motor - UL/CSA	Product Weight (pounds) :	257
Cord :	Not included	Rough-in Dimensions :	57" x 57"
Country of Origin :	US	Speed Control Compatible :	No
Diameter (inches) :	54	Speeds :	1
Display Name :	543SMCB112G-HV	Thermal Protection :	Yes
Distinguishing Feature - Fan :	Exhaust Fan c/w Cone	VFD Compatible :	No
Drive Type :	Belt	Voltage :	208-230