

## TW24B-TPQR

### 24" Oscillating OSHA Pedestal Fan



Air Velocity (@ 10') :	900	Guard Material & Coating :	Powder Coated Steel
Blade Color :	Metallic	Guard Spacing (inches) :	1/2 OSHA
Blade Material :	Aluminum	Mount Type Recommended :	NA
CFM (free air) :	5400	Nameplate Amps :	3.0/3.7
CFM (high) :	5400	Number of Wings :	3
CFM (low) :	4900	Opening Area (sq. ft.) :	NA
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Oscillating :	No
CFM Range (Free Air) :	5001 - 10000	Phase :	1
CFM/Watt (free Air) :	20.8	Power (hp) :	1/4
Component Certifications :	Motor - UL/CSA/CE	Product Color :	Black
Cord :	Included - Wired	Rough-in Dimensions :	NA
Cord Length (feet) :	10	Schaefer Performance Test No. :	694
Country of Origin :	US	Sound Level (dBA @ 10') :	64
Diameter (inches) :	20	Speed Control Compatible :	No
Display Name :	TW24B-TPQR	Speeds :	2
Drive Type :	Direct	Switch :	On product
Fixed or Portable :	Portable	VFD Compatible :	No
Frequency (Hz) :	60	Voltage :	115
Guard Color :	Black		