

TW30W

30" Oscillating Circulation Fan



Able to Ship Small Parcel :	No	Guard Color :	White
Air Velocity (@ 10') :	1100	Guard Material & Coating :	Powder Coated Steel
Blade Color :	Metallic	Guard Spacing (inches) :	1/2 OSHA
Blade Material :	Aluminum	Mount Type Recommended :	WMTA30-B, VS30FMT
CFM (free air) :	9600	Nameplate Amps :	5.9
CFM (high) :	9600	Number of Wings :	3
CFM (low) :	8500	Oscillating :	Yes
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Phase :	1
CFM Range (Free Air) :	5001 - 10000	Power (hp) :	1/2
CFM/Watt (free Air) :	20.3	Product Color :	White
Component Certifications :	Motor - CSA	Product Weight (pounds) :	62
Cord :	Included - Wired	Schaefer Performance Test No. :	701
Cord Length (feet) :	10	Sound Level (dBA @ 10') :	71
Country of Origin :	US	Speed Control Compatible :	No
Diameter (inches) :	30	Speeds :	2
Display Name :	TW30W	Switch :	On product
Drive Type :	Direct	VFD Compatible :	No
Fixed or Portable :	Fixed	Voltage :	115
Frequency (Hz) :	60		